Serial No.: 09/527,584

## AMENDMENTS TO THE CLAIMS

This listing of the claims replaces all prior versions, and listings, of claims in the application:

## LISTING OF CLAIMS

- 1. (Currently Amended) A method of managing a logical allocation of resources between connection-oriented traffic and connectionless traffic being routed through a shared physical network element of a communications network, the method comprising the steps of:
  - a) determining a resource requirement of the connection-oriented traffic; and
  - dynamically adjusting a respective connectionless traffic metric to be used for routing connectionless traffic based on the determined resource requirement of the connection-oriented traffic; and
  - c) routing the connectionless traffic based on the adjusted traffic metric.

    thereby providing the logical allocation of resources for connectionless traffic based on the resource requirement of connection-oriented traffic.
- (Original) A method as claimed in claim 1, wherein the connection-oriented traffic comprises multi-protocol label switched (MPLS) traffic.
- 3. (Original) A method as claimed in claim 2, wherein the step of determining the resource requirement of the connection-oriented traffic comprises the steps of:
  - receiving MPLS reservation requests in respect of the shared physical network element; and
  - dynamically adjusting a total amount of resources required to satisfy the received MPLS reservation requests.

- 4. (Original) A method as claimed in claim 1, wherein the connectionless traffic comprises internet protocol (IP) packet traffic.
- (Original) A method as claimed in claim 4, wherein routing of the connectionless traffic is controlled using an interior gateway protocol (IGP) routing system adapted to calculate a shortest path route of the connectionless traffic through the communications network, the shortest path routing being based on a respective metric of each physical network element forming the network.
- 6. (Original) A method as claimed in claim 5, wherein the step of dynamically adjusting the respective metric comprises the steps of:
  - increasing the respective metric as the determined resource requirement of the connection-oriented traffic increases; and
  - decreasing the respective metric as the determined resource requirement of the connection-oriented traffic decreases.
- (Original) A method as claimed in claim 5, wherein the respective metric is a link
  distance vector associated with a respective link connected to a node of the
  communications network.
- 8. (Original) A method as claimed in claim 7, wherein the step of dynamically adjusting the respective metric comprises the steps of:
  - a) determining an updated value of the link distance vector; and
  - b) updating a mapping table maintained by the node with the updated value of the link distance vector.
- 9. (Original) A method as claimed in claim 8, wherein the step of determining an updated value of the link distance vector comprises a step of querying a resource allocation table comprising a plurality of characteristic resource allocation values

Serial No.: 09/527,584

and a respective link distance vector value corresponding to each characteristic resource allocation value.

- 10. (Original) A method as claimed in claim 9, wherein the step of querying the resource allocation table comprises the steps of:
  - a) identifying the characteristic resource allocation value which most closely matches the determined resource requirement of the connection-oriented traffic; and
  - b) selecting the corresponding link distance vector as the updated link cost factor.
- 11. (Original) A method as claimed in claim 5, wherein the respective metric is a link cost factor associated with a respective link connected to a node of the communications network.
- 12. (Previously Presented) A method as claimed in claim 10, wherein the step of dynamically adjusting the respective metric comprises the steps of:
  - a) determining an updated value of the link cost factor;
  - b) updating a PATH table maintained by the node with the updated link cost factor value; and
  - c) propagating a link state packet containing the updated link cost factor value to neighboring nodes within the network.
- 13. (Original) A method as claimed in claim 12, wherein the step of determining an updated value of the link cost factor comprises a step of querying a resource allocation table comprising a plurality of characteristic resource allocation values and a respective link cost factor value corresponding to each characteristic resource allocation value.

Serial No.: 09/527,584

- 14. (Original) A method as claimed in claim 13, wherein the step of querying the resource allocation table comprises the steps of:
  - a) identifying the characteristic resource allocation value which most closely matches the determined resource requirement of the connection-oriented traffic; and
  - b) selecting the corresponding link cost factor as the updated link cost factor.
- 15. (Currently Amended) A shared network element operative within a communications network capable of end-to-end transport of connection-oriented traffic and connectionless traffic through the shared network element, the shared network element comprising:
  - means for determining a resource requirement of the connection-oriented traffic; and
  - b) means for dynamically adjusting a respective connectionless traffic metric to be used for routing connectionless traffic based on the determined resource requirement of the connection-oriented traffic; and
  - c) means for routing the connectionless traffic through the shared network element based on the adjusted traffic metric.

thereby providing a logical allocation of resources for connectionless traffic based on the resource requirement of connection-oriented traffic.

- 16. (Original) A shared network element as claimed in claim 15, wherein the connection-oriented traffic comprises multi-protocol label switched (MPLS) traffic.
- 17. (Original) A shared network element as claimed in claim 16, wherein the means for determining the resource requirement of the connection-oriented traffic comprises:
  - means for receiving MPLS reservation requests in respect of the shared physical network element; and

- b) means for dynamically adjusting a total amount of resources required to satisfy the received MPLS reservation requests.
- (Original) A shared network element as claimed in claim 15, wherein the connectionless traffic comprises internet protocol (IP) packet traffic.
- 19. (Original) A shared network element as claimed in claim 18, wherein routing of the connectionless traffic is controlled using an interior gateway protocol (IGP) routing system adapted to calculate a shortest path route of the connectionless traffic through the communications network, the shortest path routing being based on a respective metric of each physical network element forming the network.
- 20. (Original) A shared network element as claimed in claim 19, wherein the means for dynamically adjusting the respective metric comprises means adapted to:
  - a) increase the respective metric as the determined resource requirement of the connection-oriented traffic increases; and
  - decrease the respective metric as the determined resource requirement of the connection-oriented traffic decreases.
- 21. (Original) A shared network element as claimed in claim 19, wherein the respective metric is a link distance vector associated with a respective link connected to a node of the communications network.
- 22. (Original) A shared network element as claimed in claim 21, wherein the means for dynamically adjusting the respective metric comprises:
  - a) means for determining an updated value of the link distance vector; and
  - b) means for updating a mapping table maintained by the shared network element with the updated value of the link distance vector.

- (Original) A shared network element as claimed in claim 22, wherein the means for determining an updated value of the link distance vector comprises a resource allocation table comprising a plurality of characteristic resource allocation values and a respective link distance vector value corresponding to each characteristic resource allocation value.
- 24. (Original) A shared network element as claimed in claim 23, further comprising:
  - means for identifying the characteristic resource allocation value which most closely matches the determined resource requirement of the connection-oriented traffic; and
  - means for selecting the corresponding link distance vector as the updated link cost factor.
- 25. (Original) A shared network element as claimed in claim 19, wherein the respective metric is a link cost factor associated with a respective link connected to a node of the communications network.
- 26. (Previously Presented) A shared network element as claimed in claim 25, wherein the means for dynamically adjusting the respective metric comprises:
  - a) means for determining an updated value of the link cost factor;
  - b) means for updating a PATH table maintained by the node with the updated link cost factor value; and
  - c) means for propagating a link state packet containing the updated link cost factor value to neighboring nodes within the network.
- 27. (Original) A shared network element as claimed in claim 26, wherein the means for determining an updated value of the link cost factor comprises a resource allocation table comprising a plurality of characteristic resource allocation values and a

Serial No.: 09/527,584

respective link cost factor value corresponding to each characteristic resource allocation value.

- 28. (Original) A shared network element as claimed in claim 27, further comprising:
  - means for identifying the characteristic resource allocation value which most closely matches the determined resource requirement of the connection-oriented traffic; and
  - b) means for selecting the corresponding link cost factor as the updated link cost factor.
- 29. (Currently Amended) A method of managing a logical allocation of resources between connection-oriented traffic and connectionless traffic being routed through a shared physical network element of a communications network, the method comprising the steps of:
  - a) in response to a change in resources allocated to a multi-protocol label switched (MPLS) path through the shared physical network element, determining an updated total amount of resources of the shared physical network element allocated to connection-oriented traffic; and
  - b) dynamically adjusting a respective updated connectionless traffic metric of the shared physical network element based on the updated total resources allocated to the connection-oriented traffice; and
  - c) routing the connectionless traffic based on the adjusted traffic metric.
- 30. (Currently Amended) A shared network element operative within a communications network capable of end-to-end transport of connection-oriented traffic and connectionless traffic through the shared network element, the shared network element comprising:

- a) means responsive to a change in resources allocated to a multi-protocol label switched (MPLS) path through the shared physical network element for determining an updated total amount of resources of the shared physical network element allocated to connection-oriented traffic; and
- b) means for determining an updated connectionless traffic metric to be used for routing connectionless traffic based on the updated total resources allocated to the connection-oriented traffic.: and
- c) means for routing the connectionless traffic based on the adjusted traffic metric.